

# VMX-agility™

Application Driven Compact Soft Starter

200 - 600VAC, 17 - 361A, 3 - 350HP

*IEC Rated Soft Starter*



**OLED**

Display  
Event History  
with real-time  
clock

**3S**

Smooth start and  
stop with stable  
acceleration  
and deceleration

**6**

Operation  
Languages  
to choose from

**OL**

Motor Protection  
with Thermal  
Memory Feature

**Connect**

2 DI / 2 DO  
Modbus RTU  
USB

**APPS**

23 Pre-loaded  
Applications  
to choose from

**Fire Mode**

Continue running  
to destruction  
in Emergency  
Situations

**Bypass**

Internal Bypass  
is Standard on  
all Sizes



## Full Featured – Compact - Application Driven

VMX-agility™ has been developed to exceed the exacting demands of industrial automation motor control clients. VMX-agility™ delivers stable, structured start and stop ramps for smooth, efficient performance. One standard frame size covers all typical applications from 3 -350 HP at 200 - 600 VAC.



### Motor Overload Protection

Protecting the motor and soft starter in the event of an overload condition at full I<sup>2</sup>t motor overload with intelligent thermal memory retention feature. Continually monitoring overloads to ascertain the reduction in motor heating levels even when VMX-agility™ is in the 'off' state. This is combined with protection and diagnostics giving the operator peace of mind while running the motor.



### Event Logging

VMX-agility™ life event logging is a unique feature that records the last 1600 events to enable fast accurate fault analysis and their resolution. Recording multiple activities including start, stop, top of ramp, faults, application parameters (time, overload level, currents, frequency) and the device information. Event log can be downloaded via USB port or via the VMX-agility commissioning software.



### Soft Stopping

Eliminate Water Hammer with Soft Stop Control. A gradual reduction in the output torque of your pump motor is provided when a stop signal is initiated. Check valves close gently and other fluid system components are no longer subjected to the shock and destructive potential of water hammer.



- 1. OLED display**  
Full text messages enabling fast programming and rapid fault finding with no codes and real-time value monitoring. Local display of recent logged events.
- 2. Modbus RTU**  
Modbus RTU communications as standard. No optional communication cards required.
- 3. USB Port**  
USB port for downloading event log and firmware updates.

## More Design Features

### Control Circuit

A standard 24 VDC control voltage supply with an optional power module which adapts the digital input voltage to accept a 110–230 VAC signal.

### Start Delay Feature

Intentional start delay allowing pump actuators to engage before start.

### Lower Panel Production Costs

The VMX-agility™ uses one common unit frame size across the voltage range of 200–600 VAC facilitating efficient panel layout and interconnections to reduce material and panel production time.

### Loss Reduction

An integral bypass is initiated at the top of ramp and reduces losses in the soft starter.

### Fire Mode


External input signal overriding normal controls allowing the motor to continue running in emergency situations.

### Number of Starts


Optional cooling fan for heavy duty applications with up to 40 starts per hour.

With 23 pre-programmed applications profiles, the VMX-agility™ offers a quick and comprehensive commission process. A typical VMX-agility™ setup takes less than 1 minute whereas a comparable competitive product setup could take anywhere from 60 to 120 minutes depending on the application. Access to an advanced setup menu is standard for special application requirements.

## Typical Applications



Conveyors



Pumps



Fans



Compressors



Crushers

## 3S Technology

Automatic ramp control profiles ensure smooth start and stop performance, delivering stable acceleration and deceleration in all operating conditions.





# Easy to Install and Easy to Wire

## Specifications

<b>Operational Voltage</b>	200 - 600 VAC
<b>Rated Frequency</b>	50 - 60 Hz $\pm$ 5 Hz
<b>Index Rating</b>	Trip Class 10: 3.5-17: 90-5 (Trip Class 20 & 30)
<b>Starts per Hour Standard</b>	5 starts/stops per hour (40 with Fan Option)
<b>Internally Bypassed</b>	Yes
<b>Screen</b>	OLED
<b>Control Supply</b>	Standard 24 VDC 110 to 230 VAC with Power Supply Option
<b>Inputs</b>	2 Digital Inputs, 1 Programmable
<b>Overload</b>	Full I2t Motor Overload with Memory
<b>Communications</b>	Modbus RTU
<b>Full Logging functionality with commissioning software</b>	YES
<b>IP/NEMA rating</b>	IP20/NEMA Class 1 (*with finger guard fitted)
<b>Ambient Temperature</b>	-4° ~ 104°F (-20 ~ 40°C) without de-rating 140°F (60°C) with de-rating
<b>Standards</b>	CE, UL, RCM
<b>Languages</b>	English, French, German, Spanish, Portuguese, Italian
<b>Warranty</b>	2 Years

## VMX-agility Options



### Remote Display Keypad

Plug in remote mounting unit keypad mimics the agility™ display and keypad function. IP65/NEMA Class 4X



### Power Supply Unit Module

Unique to VMX-agility™ this module enables control voltage options in one standard product unit, no need to purchase separate soft starters for different control voltages.



### Cooling Fan

For use in frequent duty applications with up to 40 starts per hour.

# VMX-agility™ Series

# Rugged - Compact - Versatile

## Ratings

Model Number	Amps
VMX-AGY-101	17
VMX-AGY-103	22
VMX-AGY-105	27
VMX-AGY-107	34
VMX-AGY-109	41
VMX-AGY-111	52
VMX-AGY-113	65
VMX-AGY-201	77
VMX-AGY-203	100
VMX-AGY-205	125
VMX-AGY-207	156
VMX-AGY-209	192
VMX-AGY-301	242
VMX-AGY-303	302
VMX-AGY-305	361

## Sizing Guide

Amps	Nominal Motor HP Rating					Trip Class 10 AC-53a 3.5-17: 90-5 <sup>4</sup>	Trip Class 20 AC-53a 4-19: 90-5 <sup>4</sup>	Trip Class 30 AC-53a 4-29: 90-5 <sup>4</sup>
	200V	208V	240V	480V	575V			
17	3	5	5	10	15	-	-	VMX-AGY-101
17	3	5	5	10	15	-	VMX-AGY-101	VMX-AGY-103
17	3	5	5	10	15	VMX-AGY-101	VMX-AGY-103	VMX-AGY-105
22	5	5	7.5	15	20	VMX-AGY-103	VMX-AGY-105	VMX-AGY-107
27	7.5	7.5	7.5	20	25	VMX-AGY-105	VMX-AGY-107	VMX-AGY-109
34	10	10	10	25	30	VMX-AGY-107	VMX-AGY-109	VMX-AGY-111
41	10	10	10	30	40	VMX-AGY-109	VMX-AGY-111	VMX-AGY-113
52	15	15	15	40	50	VMX-AGY-111	VMX-AGY-113	VMX-AGY-201
65	20	20	20	50	60	VMX-AGY-113	VMX-AGY-201	VMX-AGY-203
77	20	25	25	60	75	VMX-AGY-201	VMX-AGY-203	VMX-AGY-205
100	30	30	30	75	100	VMX-AGY-203	VMX-AGY-205	VMX-AGY-207
125	40	40	40	100	125	VMX-AGY-205	VMX-AGY-207	VMX-AGY-209
156	50	50	60	125	150	VMX-AGY-207	VMX-AGY-209	VMX-AGY-301
192	60	60	60	150	200	VMX-AGY-209	VMX-AGY-301	VMX-AGY-303
242	75	75	75	200	250	VMX-AGY-301	VMX-AGY-303	VMX-AGY-305
302	100	100	100	250	300	VMX-AGY-303	VMX-AGY-305	-
361	125	125	150	300	350	VMX-AGY-305	-	-

## Dimensions and Weights

Model Number	Dim. H x W x D inches (mm)	Weight lbs. (kg)
VMX-AGY-101 thru 113	7.13 (181) x 4.25 (108) x 5.83 (148)	4.34 (1.97)
VMX-AGY-201 thru 209	11.65 (296) x 5.78 (147) x 9.37 (238)	13.89 (6.3)
VMX-AGY-301 thru 305	19.29 (490) x 8.07 (205) x 13.03 (331)	33.07 (15)



### CORPORATE HEADQUARTERS

#### Motortronics / Phasetronics

1600 Sunshine Drive  
 Clearwater, Florida 33765  
 Tel: 727.573.1819 or 888.767.7792  
 Fax: 727.573.1803 or 800.548.4104  
 E-mail: sales@motortronics.com  
 www.motortronics.com

### INTERNATIONAL LOCATIONS

#### Fairford Electronics Ltd.


Bristow House,  
 Gillard Way, Ivybridge,  
 Devon, PL21 9GG,  
 United Kingdom  
 Tel: +44 (0)1752 894554  
 www.fairford.com

#### Motortronics Int'l Korea Co Ltd

601, Daeryung Techno Tower 5-cha  
 Gasan-dong, Geumcheon-gu  
 Seoul, Korea 9153-774  
 Tel: 82-2-867-5808 / Fax: 82-2-867-6004  
 www.motortronics-korea.com

#### M & P Machinery & Electronics Control

32 Jiaxin Road, Jimo  
 Qingdao, China 266229  
 Tel: 86-532-81725028  
 Fax: 86-532-81725038  
 www.mp-cn.com



PN:VMX-AGY-071218